

Duotronic embalming machines are shipped with complete operating instructions, suggested maintenance procedures and limited warranty guidelines. It is the full responsibility of the purchaser to read this information completely before operating the machine and to adhere to all manufacturer's recommendations.

DUOTRONIC EMBALMING MACHINES

FEATURES	DUOTRONIC I	DUOTRONIC II	DUOTRONIC III
	103829	147753	147796
Injection Pressure Range (psi)	0 - 30 psi	0 -30 psi	0 - 15 psi
Adjustable Rate of Flow Control	Yes	Yes	Yes
Motor & Pump Casing	Stainless Steel	Stainless Steel	Stainless Steel
Glass Fluid Tank Capacity	3 gallons	3 gallons	3 gallons
Fluid Reservoir Bottom	Stainless Steel	Stainless Steel	Stainless Steel
Automatic Shut-Off	No	No	No
Pulsation	No	Yes	No
Motor	2 speed; 1/2 HP	2 speed; 1/2 HP	1 speed; 1/8 HP
Pump Drive	Standard drive	Standard drive	Magnetic drive
Volt/Hertz 1 Phase AC	110 V/60 hz.	110 V/60 hz.	110 V/60 hz.
Power Cord	7 ft.; polarized plug	7 ft.; polarized plug	7 ft.; polarized plug
Tubing 5/16" ID x 1/8" WT	10 ft. latex	10 ft. latex	10 ft. latex
Tubing Attachment	Quick disconnect	Quick disconnect	Quick disconnect
Manufacturer's Warranty	One year	One year	One year
Overall Height	21"	21"	21"
Overall Width	14.75"	14.75"	14.75"
Overall Length	17"	17"	17"
Weight	65 lbs.	56 lbs.	48 lbs.
Shipped with Cleaning Solution	Yes	Yes	Yes