

Porti-Boy embalming machines are shipped with complete operating instructions, suggested maintenance procedures and limited warranty guidelines. It is the full responsibility of the purchaser to read this information completely before operating the machine and to adhere to all manufacturer's recommendation.

PORTI-BOY EMBALMING MACHINES

FEATURES	MARK IV ITEM#4766	MARK V ITEM#4774
Injection Pressure Range (psi)	0 - 60 psi	0 - 100 psi
Adjustable Rate of Flow Control	Yes	Yes
Motor and Pump Casing	Cast aluminum	Cast aluminum
Finish	Nylon dipped interior & exterior	Nylon dipped interior & exterior
Glass Fluid Tank Capacity	2.5 gallons	3.25 gallons
Fluid Reservoir Bottom	Stainless steel	Stainless steel
Automatic Shut-Off	Yes	Yes
Pulsation	No	Yes
Motor	1/6 HP	1/5 HP
Pump Drive	Magnetic drive	Magnetic drive
Volt/Hertz 1 Phase AC	110 V/60 hz.	110 V/60 hz.
Heavy Duty Power Cord	8 ft.; polarized plug	8 ft.; polarized plug
Tubing 3/16" ID x 5/16" OD	10 ft. rubber with in-line stopcock	10 ft. rubber with in-line stopcock
Tubing Attachment	Quick disconnect	Quick disconnect
Manufacturer's Warranty	One year	One year
Overall Height	22.5"	24.5"
Overall Width	12"	14"
Overall Length	12"	14"
Weight	53 lbs.	53 lbs.
Shipped with Cleaning Solution	Yes	Yes